



Product Data Sheet

Blown Hand Stretch

Issue number: 1

	Tolerance	Test Method
Width	Nominal ± 5 mm	Metric Rule
Meterage/reel (no Joins)	Nominal $\pm 7.5\%$	Metric Rule
Reel Weight	Nominal $\pm 7.5\%$	
Spot Thickness	Nominal $\pm 15\%$	Micrometer
Average Thickness	Nominal $\pm 7.5\%$	Gravimetric
Roll Edge Profile	Flush	
Thickness	$>15\mu\text{m}$; the sales team can provide further details.	
Colours	A variety of colours & additives are available; the sales team can provide further details.	
Cores	A variety of cores are available; the sales team can provide further details.	
Product Composition	A blend of LLDPE (Linear low-density polyethylene) & LDPE (Low density polyethylene) containing 30% recycled content	
Recyclable	Yes. 100%. Code 4. LDPE	
Storage	The product should be stored in a dry place at a temperature not greater than 25°C and not less than 10°C to maintain stability.	
Guarantee	This product is fit for its intended use for 3 months from the date of dispatch and therefore Coveris is not able to accept any claims after this date.	

Purchaser remains responsible for determining whether the use complies with all relevant regulations. This product is classed as tertiary packaging and is not suitable for direct food contact.