



Product Data Sheet

Blown Pre-Stretch

Issue number: 1

	Tolerance	Test Method
Width	Nominal ± 40 mm	Metric Rule
Meterage/reel	Nominal $+0/-10\%$	Metric Rule
Reel Weight	Nominal $\pm 10\%$	
Spot Thickness	Nominal $\pm 20\%$	Micrometer
Average Thickness	Nominal $\pm 10\%$	Gravimetric
Roll Edge Profile	Oscillated with Folded Edges	
Thickness	5 μ m, 6 μ m, 7 μ m & 9 μ m	
Colours	A variety of colours & additives are available; the sales team can provide further details.	
Cores	A variety of cores are available; the sales team can provide further details.	
Product Composition	A blend of LLDPE (Linear low-density polyethylene) & LDPE (Low density polyethylene) containing 30% recycled content	
Recyclable	Yes. 100%. Code 4. LDPE	
Storage	The product should be stored in a dry place at a temperature not greater than 25°C and not less than 10°C to maintain stability.	
Guarantee	<p>This product is fit for its intended use for 6 months from the date of dispatch and therefore Coveris is not able to accept any claims after this date.</p> <p>Due to the nature of the manufacturing process it is possible the occasional hole may be apparent. This should not be detrimental to the wrapping process.</p> <p>Due to the nature of this film and the production methods used the film may relax by up to 10% post-production. All rolls are manufactured on calibrated machinery and within the tolerances stated on the specification sheet.</p>	

Purchaser remains responsible for determining whether the use complies with all relevant regulations. This product is classed as tertiary packaging and is not suitable for direct food contact.